



Allstate Gasket & Packing, Inc • 31 Prospect Place • Deer Park, New York 11729-3713 USA
 Email: sales@allstategasket.com • Tel: (631) 254-4050 • Fax: (631) 254-4330

Visit our www.AllstateGasket.com for more information. Prices and availability may vary. All information is provided as reference, be sure to do your own testing for product suitability. No warranties or guarantees are expressed or implied.

STYLE AFC BLUE COMPRESSED SHEET - ARAMID FIBER NITRILE BINDER

Features: AFC Blue has excellent sealing, thermal and mechanical properties and good chemical resistance within the given temperature and pressure limits - see below.

Material: Aramid fiber with nitrile binder, compressed

Color: Blue

Recommended Uses: AFC Blue is a universal gasket material suitable for general use with an extremely wide range of applications. Due to its excellent sealing properties, AFC Blue is particularly recommended for all applications in gas distribution installations (also at high temperatures). It can also be used for sealing oils, fuels, freons, solvents, non-aggressive chemicals, and many other media. Using AFC Blue provides a reliable and safe solution in a wide range of applications including pumps, compressors, boilers, and many different flanged joints.

Operating Temperature: 500°F

Sizes: 60" x 60" sheet

Thicknesses: 1/64", 1/32", 1/16", 3/32", 1/8"

See gasket material shelf life info on www.AllstateGasket.com

Material	Aramid Fiber Nitrile Binder
Maximum Operating Conditions Pressure	1,950 PSI
Sealability* ASTM-F-37	0.13
Compressibility-ASTM-F-36J	7-17
Recovery-ASTM-F-36J	50% Minimum
Thickness Increase:	0-10
ASTM Oil No. 3, 5H, 300°	0-10
ASTM Fuel 8, 5H, 73° F	